



113 - ECOLOGY 250 HD

Thermoplastic constant pressure hose for high pressure sewer cleaning applications up to 250 bar (3600 psi)



FEATURES

Inner Tube

Thermoplastic polymer

Reinforcement

Up to three braids of synthetic fiber plus one special extra braid of synthetic fiber for cover integration $% \left(1\right) =\left(1\right) +\left(1\right)$

Cover

Polyurethane - red - non pinpricked - laser branding

Applications

Modern sewer cleaning vehicles and applications requiring long lengths high working pressure and low pressure drop - Equipment used in high humidity environments

Features

Red cover impregnated into braid reinforcement for optimum wear resistance and longevity - Available in long lengths - Excellent crush and cut resistance - Lightweight compared to rubber alternatives - Cover resistant against micro-biological attack - Reduced bend radius - Fast operating speeds

Description

Heavy duty sewer cleaning hose suitable for temperatures ranging from -40 °C to 60 °C (-40 °F to 140 °F) - Hose specifically designed for working in humid conditions without degrading ensuring increased lifetime - Available with BSP and / or NPT fitting combinations - Other end terminations upon request - Not suitable for hydraulic applications - Factory made assembly - also available as loose coils: please, contact our sales office for further details

Temperature Range

-40 °C to 60 °C (-40 °F to 140 °F)

Standard Branding

TRANSFER OIL - TO INDUSTRIAL - Part No - ECOLOGY 250 HD - SEWER CLEANING HOSE - Inch Size - DN Size - WP bar / psi - MADE IN ITALY - www.transferoil.com - QQ/YY - Batch No

Part no.	DN	Inches	Dash	ID (mm)	OD (mm)	WP (bar)	BP (bar)	ID (inch)	OD (inch)	WP (psi)	BP (psi)	SF	BR (mm)	BR (inch)	Weight (gr/m)	Weight (lb/ft)	Ferrule standard	Ferrule A316L
1135	DN12	1/2	-8	13.0	22.2	250	625	0.512	0.874	3600	9000	2.5:1	75	2.95	254	0.171	SA5151	SA5851
1137	DN20	3/4	-12	19.6	30.4	250	625	0.772	1.197	3600	9000	2.5:1	120	4.72	435	0.292	SA5171	SA5871
1138	DN25	1	-16	25.6	36.5	250	625	1.008	1.437	3600	9000	2.5:1	155	6.10	580	0.390	SA5181	SA5881
1139	DN32	1+1/4	-20	32.4	46.0	250	625	1.276	1.811	3600	9000	2.5:1	240	9.45	808	0.543	SA5191	SA5891
113T	DN38	1+1/2	-24	38.4	53.4	250	625	1.512	2.102	3600	9000	2.5:1	300	11.81	1154	0.775	SA51T1	SA58TI

part no	description	fittings
EMEXXX	1/2" ECOLOGY 250 HD	1/2" M/F BSP
EMFXXX	1/2" ECOLOGY 250 HD	1/2" M/M NPT
EMQXXX	1/2" ECOLOGY 250 HD	1/2" M/F BSP - AISI A316L
EMRXXX	1/2" ECOLOGY 250 HD	1/2" M/M NPT - AISI A316L
ENGXXX	3/4" ECOLOGY 250 HD	3/4" M/F BSP
ENHXXX	3/4" ECOLOGY 250 HD	3/4" M/M NPT
ENSXXX	3/4" ECOLOGY 250 HD	3/4" M/F BSP - AISI A316L
ENTXXX	3/4" ECOLOGY 250 HD	3/4" M/M NPT - AISI A316L
EOIXXX	1" ECOLOGY 250 HD	1" M/F BSP
EOJXXX	1" ECOLOGY 250 HD	1" M/M NPT
EOUXXX	1" ECOLOGY 250 HD	1" M/F BSP - AISI A316L
EOVXXX	1" ECOLOGY 250 HD	1" M/M NPT - AISI A316L
EPKXXX	11/4" ECOLOGY 250 HD	11/4" M/F BSP
EPLXXX	11/4" ECOLOGY 250 HD	11/4" M/M NPT
EPWXXX	11/4" ECOLOGY 250 HD	1 1/4" M/F BSP - AISI A316L
EPXXXX	11/4" ECOLOGY 250 HD	1 1/4" M/M NPT - AISI A316L
E82XXX	1 1/2" ECOLOGY 250 HD	1 1/2" M/F BSP
E83XXX	1 1/2 ECOLOGY 250 HD	1 1/2" M/M NPT
	XXXtotal lenght of the assembled ho	se in meters (1mt = 3,28 ft)

Hose assembly - Without hose reel

part no	description	fittings				
FMEXXX	1/2" ECOLOGY 250 HD	1/2" M/F BSP				
FMFXXX	1/2" ECOLOGY 250 HD	1/2" M/M NPT				
FMQXXX	1/2" ECOLOGY 250 HD	1/2" M/F BSP - AISI A316L				
FMRXXX	1/2" ECOLOGY 250 HD	1/2" M/M NPT - AISI A316L				
FNGXXX	3/4" ECOLOGY 250 HD	3/4" M/F BSP				
FNHXXX	3/4" ECOLOGY 250 HD	3/4" M/M NPT				
FNSXXX	3/4" ECOLOGY 250 HD	3/4" M/F BSP - AISI A316L				
FNTXXX	3/4" ECOLOGY 250 HD	3/4" M/M NPT - AISI A316L				
FOIXXX	1" ECOLOGY 250 HD	1" M/F BSP				
FOJXXX	1" ECOLOGY 250 HD	1" M/M NPT				
FOUXXX	1" ECOLOGY 250 HD	1" M/F BSP - AISI A316L				
FOVXXX	1" ECOLOGY 250 HD	1" M/M NPT - AISI A316L				
FPKXXX	1 1/4" ECOLOGY 250 HD	1 1/4" M/F BSP				
FPLXXX	1 1/4" ECOLOGY 250 HD	1 1/4" M/M NPT				
FPWXXX	1 1/4" ECOLOGY 250 HD	1 1/4" M/F BSP - AISI A316L				
FPXXXX	11/4" ECOLOGY 250 HD	1 1/4" M/M NPT - AISI A316L				