



# **07B** - POWER WASH STEEL BLUE

Thermoplastic hose with steel reinforcement for water cleaning applications from 210 to 280 bar (from 3000 to 4000 psi)



## **FEATURES**

#### Inner tube

Thermoplastic polymer

#### Reinforcement

One braid steel wire

## Cover

Thermoplastic polymer - Blue - Non pinpricked - Laser branding

### **Applications**

Water cleaning applications such as professional power washers, car-wash stations, including self-service car-wash stations

#### **Features**

Rugged construction for HD application and extendend lifecycle - Lightweight - Compact design - High flexibility - Abrasion resistant

### Description

High pressure service hose suitable for connection between water pump and washing gun - The steel reinforcement makes this hose extremely resistant but still lightweight if compared with rubber alternatives - The construction and the pressure rating of this hose make this product the ideal choice for professional power washers or self-service car-wash stations - Also available as factory made assemblies: please contact our sales office for further details.

#### Temperature range

-20 °C to 60 °C (-4 °F to 140 °F)

#### WARNING

Not suitable for hot water or steam. Max water temperature 60°C / 140°F.

# Standard Branding

TRANSFER OIL - TO INDUSTRIAL - Part No - POWER WASH STEEL BLUE - Inch Size - DN Size - WP bar / psi - WARNING > NOT SUITABLE FOR HOT WATER OR STEAM - MAX WATER TEMP 60 C / 140 F - MADE IN ITALY - www.transferoil.com - QQ/YY - Batch No

| Part no. | DN   | Inches | Dash | ID<br>(mm) | OD<br>(mm) | WP<br>(bar) | BP<br>(bar) | ID<br>(inch) | OD<br>(inch) | WP<br>(psi) | BP<br>(psi) | SF  | BR<br>(mm) | BR<br>(inch) | Weight<br>(gr/m) | Weight<br>(lb/ft) | Ferrule<br>standard | Ferrule<br>A316L |
|----------|------|--------|------|------------|------------|-------------|-------------|--------------|--------------|-------------|-------------|-----|------------|--------------|------------------|-------------------|---------------------|------------------|
| 07B2     | DN6  | 1/4    | -4   | 6.5        | 11.9       | 280         | 1120        | 0.256        | 0.469        | 4000        | 16000       | 4:1 | 40         | 1.57         | 161              | 0.108             | SAC121              | SAC821           |
| 07B3     | DN8  | 5/16   | -5   | 8.1        | 13.6       | 210         | 840         | 0.319        | 0.535        | 3000        | 12000       | 4:1 | 55         | 2.17         | 198              | 0.133             | SAB131              | SAB831           |
| 07B4     | DN10 | 3/8    | -6   | 9.8        | 16.1       | 210         | 840         | 0.386        | 0.634        | 3000        | 12000       | 4:1 | 65         | 2.56         | 259              | 0.174             | SAC141              | SAC841           |

# **Multicolor**



Dimensions and values shown may be changed without prior notice to improve product performances and reliability.

Transfer Oil S.p.A. assumes no liability on mistakes nor errors appearing in this spec sheet.

Document date: 22/11/2025

www.transferoil.com