



## I 106 - PUSH-ON

Thermoplastic constant pressure hose for low pressure air and water line up to 20 bar (290 psi)



### FEATURES

#### Inner Tube

Polyurethane

#### Reinforcement

One braid of synthetic fiber

#### Cover

Polyurethane - Black - laser branding

#### Applications

Low pressure air and water line - Free of paint affecting substances  
- LABS free

#### Features

Polyurethane tube and cover for high flexing giving long service life - Abrasion resistant cover for optimum wear resistance - Push on fitting assembly without crimping.

#### Description

Low pressure air and water line suitable for high flexing applications.

#### Temperature Range

-40 °C to +80 °C (-40 °F to +176 °F)

Available black as standard; also available in blue, red, green, and yellow.

#### Standard Branding

**TRANSFER OIL** - TO INDUSTRIAL - Part No - PUSH-ON - Inch Size - DN Size - WP bar / psi - MADE IN ITALY - [www.transferoil.com](http://www.transferoil.com) - QQ/YY - Batch No

Part no.	DN	Inches	Dash	ID (mm)	OD (mm)	WP (bar)	BP (bar)	ID (inch)	OD (inch)	WP (psi)	BP (psi)	SF	BR (mm)	BR (inch)	Weight (gr/m)	Weight (lb/ft)	Ferrule standard	Ferrule A316L
1062	DN6	1/4	-4	6.3	11.2	20	80	0.248	0.441	290	1160	4:1	30	1.18	70	0.047		
1064	DN10	3/8	-6	9.5	15.0	20	80	0.374	0.591	290	1160	4:1	50	1.97	110	0.074		
1065	DN12	1/2	-8	12.7	19.1	20	80	0.500	0.752	290	1160	4:1	70	2.76	167	0.112		
1066	DN16	5/8	-10	16.2	23.1	20	80	0.638	0.909	290	1160	4:1	90	3.54	221	0.149		
1067	DN20	3/4	-12	19.0	26.0	20	80	0.748	1.024	290	1160	4:1	110	4.33	259	0.174		

### Multicolor



10R



10Y



10B



10G

---

*Dimensions and values shown may be changed without prior notice to improve product performances and reliability.*

*Transfer Oil S.p.A. assumes no liability on mistakes nor errors appearing in this spec sheet.*

*Document date: 24/02/2026*

*www.transferoil.com*