



TRANSFER OIL

Pure Fluid Attitude



106 - PUSH-ON

Thermoplastic constant pressure hose for low pressure air and water line up to 20 bar (290 psi)



FEATURES

Inner Tube

Polyurethane

Reinforcement

One braid of synthetic fiber

Cover

Polyurethane - Black - laser branding

Applications

Low pressure air and water line - Free of paint affecting substances
- LABS free

Features

Polyurethane tube and cover for high flexing giving long service life - Abrasion resistant cover for optimum wear resistance - Push on fitting assembly without crimping.

Description

Low pressure air and water line suitable for high flexing applications.

Temperature Range

-40 °C to +80 °C (-40 °F to +176 °F)

Available black as standard; also available in blue, red, green, and yellow.

Standard Branding

TO TRANSFER OIL - TO INDUSTRIAL - Part No - PUSH-ON - Inch Size - DN Size - WP bar / psi - MADE IN ITALY - www.transferoil.com - QQ/YY - Batch No

| Part no. | DN | Inches | Dash | ID (mm) | OD (mm) | WP (bar) | BP (bar) | ID (inch) | OD (inch) | WP (psi) | BP (psi) | SF | BR (mm) | BR (inch) | Weight (gr/m) | Weight (lb/ft) | Ferrule standard | Ferrule A316L |
|----------|------|--------|------|---------|---------|----------|----------|-----------|-----------|----------|----------|-----|---------|-----------|---------------|----------------|------------------|---------------|
| 1062 | DN6 | 1/4 | -4 | 6.3 | 11.2 | 20 | 80 | 0.248 | 0.441 | 290 | 1160 | 4:1 | 30 | 1.18 | 70 | 0.047 | | |
| 1064 | DN10 | 3/8 | -6 | 9.5 | 15.0 | 20 | 80 | 0.374 | 0.591 | 290 | 1160 | 4:1 | 50 | 1.97 | 110 | 0.074 | | |
| 1065 | DN12 | 1/2 | -8 | 12.7 | 19.1 | 20 | 80 | 0.500 | 0.752 | 290 | 1160 | 4:1 | 70 | 2.76 | 167 | 0.112 | | |
| 1066 | DN16 | 5/8 | -10 | 16.2 | 23.1 | 20 | 80 | 0.638 | 0.909 | 290 | 1160 | 4:1 | 90 | 3.54 | 221 | 0.149 | | |
| 1067 | DN20 | 3/4 | -12 | 19.0 | 26.0 | 20 | 80 | 0.748 | 1.024 | 290 | 1160 | 4:1 | 110 | 4.33 | 259 | 0.174 | | |

Multicolor



10R



10Y



10B



10G

*Dimensions and values shown may be changed without prior notice to improve product performances and reliability.
Transfer Oil S.p.A. assumes no liability on mistakes nor errors appearing in this spec sheet.
Document date: 26/05/2026
www.transferoil.com*